




A GLOBAL BRAND, MADE IN INDIA.

BR88UE / BR88UB / BR88UW

POS Receipt Printer



PRODUCT FEATURES

- Compact design, Easy to load paper
- Supports multi 1D barcode and QR code printing
- Support printer status monitoring function
- Support printing queuing ticket function
- Supports bitmap download and print
- Support different interface combination
- Up to 260mm/s high speed, low noise printing
- 48 or 80mm adjustable paper separator for option
- 150KM long life printer head
- Wall mounting support



FOR TECHNICAL SUPPORT
1800 8899 246

www.boxp.in

SPECIFICATIONS

Model	BR88UE		BR88UB	BR88UW
Interface	USB+LAN		USB+BT	USB+WiFi
Power supply	Input: AC 100V-240V, 50-60Hz, Output: DC 24V/2.5A			
Cash drawer	DC 24V/1A			
Printer head lifespan	150 KM			
Cutter	Auto cutter			
Sensors	Paper Cutter, Cover open, Cutter Jam, Paper Jam and Black Mark detection(optional)			
Accessories	Data cable, Power Adaptor, Power Cord, Paper roller, CD, Manual, paper Separator(optional)			
OS supporting	Compatible with iOS/ Android/ Windows/Linux			
Safety standards	CE, FCC, Rohs etc			
Printing capability				
Printing method	Direct thermal line			
Resolution	203 DPI			
Printing speed	260mm/s	260mm/s		260mm/s
Print width	72mm			
Graphics printing	Supports bitmap download and print (each bitmap size Max.20K)			
Printing command	Compatible with ESC/POS			
Barcode and character				
Barcode	1D barcode: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/ CODE93/CODE128 2D barcode: QR CODE(Single USB or UR solution no QR code function)			
Character size	ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm FontB: 9*17dots,1.1(W)*2.1(H)mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm			
Japanese/Korea optional	Support			
User-defined language	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/ East Europe/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151, 1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/ (PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)			
Media				
Paper type	Thermal roll paper			
Paper width	48mm/52mm/56mm/64mm/68mm/76mm/80mm (optional)			
Paper thickness	0.06~0.08mm			
Paper roll diameter	80mm Max			
Paper separator	Support			
Physical Parameters				
Dimension	180*142*136mm			
Weight	960 gm			
Package box	228*215*165mm/1.8Kg			
8 in 1 carton	475*445*358mm/16.5kg			
Environment				
Working temperature & humidity	0 to 45°C, 10%~80% No condensation			
Storage temperature& humidity	-20 to 60°C, 10%~90% No condensation			