



A GLOBAL BRAND, MADE IN INDIA.


BPS110

1D LASER SCANNER



PRODUCT FEATURES

- Advanced decoding chip for reading a wide range of 1D codes
- High-resolution laser scanning engine
- Scan rate of at least 150 scans per second
- Durable design, withstands multiple 1.5-meter drops onto concrete
- Easy plug-and-play setup with quick and simple pairing



FOR TECHNICAL SUPPORT
1800 8899 246

www.boxp.in

Specifications

Model : BPS110	
Performance Parameters	
Light Sources	650nm laser (Safe visible laser diode)
Supported Symbologies	UPC- A, UPC-E, EAN-13, EAN-8, Codabar, Code 39, Code 39 Full ASCII, Plessey, MSI, Code 93, Code 128, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, Code 11, ISBN, SSN, Code 32(Italian pharma code), Code 39 extended, GS1-128 and ITF-14, SISAS, GS1 Omnidirectional, GS1 Limited, Aviation25, RSS 14.
Scan Type	Single Laser
Scan Speed	≥150times/s
Scan Mode	Manual/Continuous/Automatic
Precision	≥3mil
Depth of scan field	20-280mm(0.33mm, PCS90%)
Scan Angle	Yaw 55°, Rotation 30°, Pitch 65°
Error Rate	1/5million
Interface	USB-HID, USB-COM, PS2, RS232
Physical Parameters	
Dimensions	83mm*70mm*172mm
Weight	128.5g
Box Dimensions (WxLxH)	20.5cm x 10cm x 8cm
Material	ABS+PC
Cable Length	2M
Environmental Parameters	
Operating Temperature	-20°C~50°C
Storage Temperature	-40°C~70°C
Relative Humidity	5% ~95% RH(Non-condensing)
Shock Resistance	Withstands multiple times 1.5 meters drops to concrete
Electronic Parameters	
Working Voltage	DC5V±1%
Operating Current	8.5mA.