



A GLOBAL BRAND, MADE IN INDIA.

BR80UE

POS Receipt Printer



USB



Wi-Fi



BLUETOOTH



LAN



PRODUCT FEATURES

- Compact design, Easy to load paper
- Supports multi 1D barcode and QR code printing
- Support different interface combination
- Up to 230mm/s high speed, low noise printing
- 58 or 80mm adjustable paper separator for option
- 100KM long life printer head



FOR TECHNICAL SUPPORT
1800 8899 246

www.boxp.in

SPECIFICATIONS

Model	BR80UE
Interface	USB+LAN
Power supply	Input: AC 100V-240V, 50-60Hz, Output: DC 24V/1.25A
Printer head lifespan	100KM
Cutter	Auto cutter with 1million time
Sensors	Print head temperature detection, paper presence detection, open cover detection, paper jam detection
Accessories	Data cable, power adaptor, power cord, paper roll, Manual, Paper separator(optional)
OS supporting	Compatible with iOS/ Android/ Windows/ Linux
Printing capability	
Printing method	Direct thermal line
Resolution	203 DPI
Printing speed	200mm/s
Print width	72mm
Input buffer	128kbytes
NV Flash	256kbytes
Graphics printing	Supports bitmap download and print (each bitmap size Max.20K)
Printing Command	Compatible with ESC/POS
Barcode and character	
Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/ CODE93/CODE128 2D barcode: QR CODE
Character size	ANK character, Font A: 2*24dots, 1.5(W)*3.0(H) mm Font B: 9*17dots, 1.1(W)*2.1(H)mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Japanese/Korea	Support (optional)
User-defined language	Support (optional)
Media	
Paper type	Thermal roll paper
Paper width	58/80mm (optional)
Paper separator	58mm/80mm (optional)
Paper Thickness	0.06~0.08mm
Paper roll diameter	80mm Max
Physical Parameters	
Dimension	173*128*131mm
Weight	850gm
Box Dimension (LxWxH)	25cm x 14cm x 15cm
Environment	
Working temperature& humidity	0 to 45°C, 10%~80% No condensation
Storage temperature& humidity	-20 to 60°C, 10%~90% No condensation