




A GLOBAL BRAND, MADE IN INDIA.

BR88UE / UB / UW

POS Receipt Printer



PRODUCT FEATURES

- Compact design, Easy to load paper
- Up to 260mm/s high speed, low noise printing
- 48 or 80mm adjustable paper separator for option
- 150KM long life printer head
- Supports multi 1D barcode and QR code printing
- Support printer status monitoring function
- Support printing queuing ticket function
- Supports bitmap download and print
- Support different interface combination
- Wall mounting support



FOR TECHNICAL SUPPORT
1800 8899 246

www.boxp.in

SPECIFICATIONS

Model	BR88UE	BR88UB	BR88UW
Interface	USB+LAN	USB+BT	USB+WiFi
Power supply	Input: AC 100V-240V, 50-60Hz, Output: DC 24V/2.5A		
Cash drawer	DC 24V/1A		
Printer head lifespan	150 KM		
Cutter	Auto cutter		
Sensors	Paper Cutter, Cover open, Cutter Jam, Paper Jam and Black Mark detection(optional)		
Accessories	Data cable, Power Adaptor, Power Cord, Paper roller, CD, Manual, paper Separator(optional)		
OS supporting	Compatible with iOS/ Android/ Windows/Linux		
Safety standards	CE, FCC, Rohs etc		
Printing capability			
Printing method	Direct thermal line		
Resolution	203 DPI		
Printing speed	260mm/s		
Print width	72mm		
Graphics printing	Supports bitmap download and print (each bitmap size Max.20K)		
Printing command	Compatible with ESC/POS		
Barcode and character			
Barcode	1D barcode: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/ CODE93/CODE128 2D barcode: QR CODE(Single USB or UR solution no QR code function)		
Character size	ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm FontB: 9*17dots, 1.1(W)*2.1(H)mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm		
Japanese/Korea optional	Support		
User-defined language	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/ East Europe/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151, 1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/ (PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)		
Media			
Paper type	Thermal roll paper		
Paper width	48mm/52mm/56mm/64mm/68mm/76mm/80mm (optional)		
Paper thickness	0.06~0.08mm		
Paper roll diameter	80mm Max		
Paper separator	Support		
Physical Parameters			
Dimension	180mm x 142mm x 136mm		
Weight	960 gm		
Box Dimensions (LxWxH)	23cm x 22cm x 17cm		
Environment			
Working temperature & humidity	0 to 45°C, 10%~80% No condensation		
Storage temperature& humidity	-20 to 60°C, 10%~90% No condensation		