



A GLOBAL BRAND, MADE IN INDIA.

BR85UE/UB/UW

POS RECEIPT PRINTER



PRODUCT FEATURES

- High-speed printing at 230mm/s with low noise
- Wall-mountable design
- Call reminder and error alert function
- Print head over-temperature protection
- Supports QR code and PDF417 printing
- IAP (In-Application Programming) online upgrade



FOR TECHNICAL SUPPORT
1800 8899 246

www.boxp.in





A GLOBAL BRAND, MADE IN INDIA.

SPECIFICATIONS

Model	BR85UE	BR85UB	BR85UW
Interface	USB+LAN	USB+BT	USB+WiFi
Printing method	Direct Thermal		
Printing Speed	230mm/s		
Paper Width	79.5±0.5mm		
Paper Thickness	0.06-0.08mm		
Column Capacity	576 dots/line or 512 dots/line		
Line Spacing	3.75mm (Adjustable by commands)		
Character size	ANK, Font A: 1.5*3.0mm (12*24 dots) Font B:1.1*2.1mm (9*17 dots)		
Barcode Character			
Extension character sheet	PC437(Std.Europe) / (Katakana;)/PC850(Multilingual)/PC860(Portugal) / PC863(Canadian)/ PC865(Nordic) / (West Europe) / (Greek) / (Hebrew) / (East Europe) / (Iran) / (WPC1252) / PC866(Cyrillic#2) / PC852(Latin2)/(PC858)/(IranII) / (Latvian) /(Arabic) / (PT1511251)		
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128		
2D Barcode	QRCODE/PDF417		
Input buffer	96 Kbytes	96 Kbytes	256 Kbytes
NVFlash	256 Kbytes		
Power			
Power adaptor Input	AC100~240V, 50~60Hz		
Printer Input	DC24V/2.5A		
Cash drawer	DC24V/1A		
Physical Characteristics			
Weight	0.85 Kg		
Dimensions	173*127*130mm	Box Dimensions (LxWxH) : 21.5cm x 19.5cm x 14.5cm	
Environmental Requirements			
Work environment	Temperature (0~45℃), humidity (10~80%)		
Storage environment	Temperature (0~60℃), humidity (10~90%)		
Reliability			
Auto cutter	Partial		
Cutter life	1.5 million cuts		
Printerhead life	150Km		
Software			
Emulation	ESC/POS		
Driver	Windows/ Linux		
Utility	Windows & Linux Test Utility		