



A GLOBAL BRAND, MADE IN INDIA.

BR95UE

POS Receipt Printer



USB



LAN



PRODUCT FEATURES

- New cover open lever design
- Thermal Line print method
- Anti insect case design
- Compact Size
- Online upgradable Firmware & Fonts
- Multi OS support



FOR TECHNICAL SUPPORT
1800 8899 246

www.boxp.in

SPECIFICATIONS

Model	BR95UE
Printing Method	Thermal Line Printing
Printing Resolution	8 dots/mm (203dpi), 576dots/line
Printing Speed	160mm/s(Max)
Effective Printing Width	72mm
Paper Width	79.5±0.5mm
Custom Characters	Support
Graphic Printing	Supports bitmap printing with different densities and downloadable graphics printing
Fonts	ASCII: 12X24 dots, 24X24 dots, 9X17 dots
Barcode	1D: UPCA, EAN-13, EAN-8, CODE39, ITF25, CODABAR, CODE93, CODE128
	2D: PDF417, QRCODE, Data Matrix
Interface	USB/USB+Ethernet
Cash Drawer Control	DC24V,1 A; 6 PIN RJ-11 socket
Power Supply	DC24V ± 5%, 1A; Power Adapter EU Standard / US Standard /UK Standard
Supported Functions	Buzzer, Open/Close Cover Alert, Paper-Out Alert, Overheat Protection, Anti-insect
PaperType	Normal Thermal Paper, 79.5* 80mm diameter (MAX)
Paper Thickness	0.06mm~0.08mm
Paper Loading Method	Easy Paper Loading
Paper Output Direction	Top Paper Output
Paper Cutting Method	Auto Cut (Partial Cut)
Physical Dimensions	125mm x 120mm x 128mm (L x W x H)
Weight	565g (without paper roll)
Command	ESC/POS
OS Compatibility	Windows / Android / Linux / Mac / IOS
Environmental Requirements	Operating Temperature: 0°C to 50°C (32°Fto 122°F)
	Operating Humidity: 10% ~ 85% RH
	Storage Temperature: -20°C to 60°C (-4°F to 140°F)
	Storage Humidity: 10% ~ 90% RH
Printhead / Cutter Life	100km / 1,000,000 cuts